

Tank dispenser Compact series

These tanks are designed to contain additives using as little space as possible. They must be installed in special storage areas.



Tank capacity:

- 2000 LITERS
- 3000 LITERS
- 5000 LITERS
- 11600 LITERS

Containment only /EA v.



With integrated dispenser /GE/EC v.

VERSIONS

- /EA: dispenser or dispensing group absent
- /GE: dispenser for internal non-metrological use
- /EC: dispenser for sale to retail fuel dispenser

TECHNICAL CHARACTERISTICS

Supporting structure	Galvanized FE430B steel without welding			
Walls and roofing	Insulated panels containing foam layer of self-extinguishing, double-walled polyurethane resins, in pre-painted steel. White color Thickness: 25 mm			
Walkable flooring	Insulated almond aluminum sheet. Thickness: 3 mm + (1.5 mm)			
Handling	By forklift, with empty tank			
Tank material	High density linear polyethylene or stainless steel (on request)			
Tank capacity	2000 l	3000 l	5000 l	11600 l
Dimensions	1,50x2,32 H2,20 m	1,78x2,75 H2,20 m	2,00x2,94 H2,20 m	2,40x4,00 H2,55 m
Weight	600 Kg	650 Kg	800 Kg	1200 Kg
Level indicator	Indication of content (in cm and liters)			
Delivery pump	Parts in contact with the product in stainless steel			
Flow rate	40 ÷ 50 l/min			
Power supply	230 VAC			
Maximum current (In)	Max 3 KW			
Pump motor power supply	230 VAC 0,74 KW			
Heating (opt.)	230 VAC 1200 W			
Ventilation	230 VAC 60 W			
Electronics	24 VAC 50 W			
Operating temperature	-20°C ÷ +40°C (+60°C on request)			

AT30/U INTEGRATED DISPENSER (if present)

Delivery flow rate	2 ÷ 30 l/min
Measurement accuracy	± 1,5 % GE version; ± 0,5% MID EC version
Computing head	CPTH02
System interface	Serial or parallel (see option)
Indicator	6-digit height 1" backlit display
Totalizer	Electronic and electromechanical non-resettable type, 7 digits
Delivery nozzle	Elaflex automatic type ZVA AdBlue® HV for heavy vehicles, ZVA AdBlue® LV for light vehicles
Hose delivery	Length 5.5 m with hose reel
Hose-reel	Made of AISI 304 stainless steel with EPDM gaskets

CODES

AT09906	Capacity	Containment	Dispenser	Dispenser type
	/200: 2000 l /300: 3000 l /500: 5000 l /116: 11600 l	/V: with containment basin /N: without containment basin	/EA: dispenser or delivery group absent /GE: dispenser for internal non-metrological use /EC: dispenser for sale to retail fuel dispenser	/SF: single frontal /SD: single right /SS: single left /DD: double /AX: alternate

AX: AA (Alternate Double Sided (1 nozzle for side)), AS (Alternate Single Sided Left), AD (Alternate Single Sided Right), AF (Alternate Single Sided Front), AB (Alternate Double Sided (2 nozzles for side))

Specifica soggetta a modifiche senza preavviso