

Tank dispenser Naked series

These tanks are designed to contain additives using as little space as possible. They are made for internal use.



Tank capacity:

- 2000 LITERS
- 3000 LITERS
- 5000 LITERS

TECHNICAL CHARACTERISTICS

Supporting structure	Painted FE430B steel		
Handling	By forklift, with empty tank		
Tank material	High density linear polyethylene or stainless steel (on request)		
Tank capacity	2000 l	3000 l	5000 l
Dimensions	1,75x2,40	1,90x2,45	1,85x3,20
Level indicator	Indication of content (in cm and liters)		
Delivery pump	Parts in contact with the product in stainless steel		
Flow rate	40 ÷ 50 l/min		
Power supply	230 VAC		
Maximum current (In)	Max 3 KW		
Pump motor power supply	230 VAC 0,74 KW		
Heating (opt.)	230 VAC 1.200 W		
Ventilation	230 VAC 60 W		
Electronics	24 VAC 50 W		
Operating temperature	-20°C ÷ +40°C (+60°C on request)		

AT30/U INTEGRATED DISPENSER (if present)

Delivery flow rate	4,5 ÷ 45 l/min
Measurement accuracy	± 1,5 %
Computing head	CPTH02
System interface	Serial or parallel (see option)
Indicator	6 digit height 1 "backlit display
Totalizer	Electronic and electromechanical non-resettable type, 7 digits
Delivery nozzle	Elaflex automatic type ZVA AdBlue® HV for heavy vehicles, ZVA AdBlue® LV for light vehicles
Hose delivery	Length 5,5 m with hose reel
Hose-reel	Made of AISI 304 stainless steel with EPDM gaskets

CODES

AT03711	Capacity
	/200: 2000 l
	/300: 3000 l
	/500: 5000 l

Specifica soggetta a modifiche senza preavviso